Attorney No. 129843-1104 Customer No. 60148 SUPPLEMENTAL AMENDMENT Application No. 10/648,009

2

Amendments to the Specification

Please replace paragraph [0014] of the as-filed specification with the re-written paragraph provided below.

-- [0014] About 93.5 grams of a type F fly ash ground to an average size of about 1.3 microns was mixed with about 5 grams of solid sodium hydroxide (flakes), about 1.5 grams of a commercial grade silicon carbide, and about 37.4 ml of water. The composition of the fly ash is given in Table 1 Table 12A. The mixture was blended into a homogeneous slurry, poured into a flat dish and allowed to solidify at room temperature for about 5 minutes. The resulting product was further dried at about 50°C for about 20 hours, after which it was ground and sieved to obtain powders within a size range of about 106 to 180 microns. In the next step, the powders were fed into a vertical heated tube furnace at an approximate feed rate of about 0.14 grams/min. The gas flow inside the tube furnace is was about 1 litre of air plus 3 litres of nitrogen per minute. The constant temperature zone of the furnace was adjusted to provide residence times from less than a second to approximately a few seconds at the peak firing temperatures. The foamed microspheres were collected on a funnel shaped collecting device covered with a fine mesh screen positioned at the bottom part of the furnace. A mild suction was applied to the end of the funnel to aid in collecting the microspheres. The products were characterized for particle density (e.g. apparent density), percent of water floatation, and approximate particle diameter distribution. The results for various firing temperatures and residence times are summarized in Table 12B Table 12. FIGS. 15 and 16 show the cross section of the products.

Table 12. Table 12A

LOI	SiO ₂	Al ₂ O ₃	Fe ₂ O	CaO	MgO	SO ₃	Na ₂ O	K ₂ O	TiO ₂	Mn ₂ O ₃	P ₂ O ₅	Total
0.40	61.53	17.91	4.72	7.30	2.91	0.40	2.16	1.39	0.86	0.08	0.28	99.94

All amounts are in percentage of weight

SUPPLEMENTAL AMENDMENT Application No. 10/648,009

Attorney No. 129843-1104 Customer No. 60148

3

Table 12. Table 12B

Temperature	Residence time	Apparent density	Water float	Size of microspheres	
(degree C)	(second)	(g/cm^3)		(micron)	
1400	0.6-1.1	0.52	83		
1300	0.6-1.1	0.49	96	130-280	
1250	0.6-1.1	0.58		105-220	

Please replace paragraph [0016] of the as-filed specification with the re-written paragraph provided below.

-- [0016] About 93.8 grams of a type F fly ash ground to an average size of about 1.3 microns was mixed with about 5 grams of solid sodium hydroxide (flakes), about 0.2 grams of a commercial grade silicon carbide, about 1 gram of commercial grade carbon black, and about 37.5 ml of water. The composition of the fly ash is given in Table 2. The mixture was blended into a homogeneous slurry, poured into a flat dish and allowed to solidify at room temperature for about 5 minutes. The resulting product was further dried at about 50°C for about 20 hours, after which it was ground and sieved to obtain powders within a size range of about 106 to 180 microns. In the next step, the powders were fed into a vertical heated tube furnace at an approximate feed rate of about 0.14 grams/min. The gas flow inside the tube furnace is was about 1 litre of air plus 3 litres of nitrogen per minute. The constant temperature zone of the furnace was adjusted to provide residence times from less than a second to approximately a few seconds at the peak firing temperatures. The foamed microspheres were collected on a funnel shaped collecting device covered with a fine mesh screen positioned at the bottom part of the furnace. A mild suction was applied to the end of the funnel to aid in collecting the microspheres. The products were characterized for particle density (e.g. apparent density), percent of water floatation, and approximate particle diameter distribution. The result is summarized in Table 12C Table 13. FIG. 17 shows the cross section of the product.

Attorney No. 129843-1104 Customer No. 60148 SUPPLEMENTAL AMENDMENT Application No. 10/648,009

4

Table 13. Table 12C

Major Oxides	Harvested	Synthetic	Synthetic	
	Cenosphere	Microsphere "A"	Microsphere "B"	
SiO ₂	62.5	58.9	65.8	
Al ₂ O ₃	25.2	17.1	12.8	
Fe ₂ O	3.7	4.5	3.3	
CaO	1.1	7.0	5.2	
MgO	1.7	2.8	2.0	
Na ₂ O	1.1	5.2	6.8	
K ₂ O	1.9	1.3	1.0	
SO ₃	0.5	0.4	0.3	
Others	2.3	2.8	2.8	